

**Product Code . SEL-EELE-11154**



## Facsimile Dynamic Demonstrator

### Description

---

#### Facsimile Dynamic Demonstrator




#### Specification:-

- Scan Method: Horizontal -Contact Image Sensor, Vertical-intermittent Scanning by stepper Motor.
- Document Size: Max – 216 X 1 000 mm , Min – 70 X 120 mm.
- Document Thickness: 0.06 – 0.15 mm.
- Type: Desktop Transceiver.
- Applicable Line: Public Switched Telephone Network.
- Compatibility: CCITT Group 3.
- Print Method: 0.06 – 0.15 mm.
- Print Method: Thermal Printing.

- 
- Recording Paper Size: 216 mm X 15M, outer diameter=40mm.
  - Recording Width: 216 mm.
  - Resolution: Horizontal – 8 dots/mm; Vertical – Standard Mode – 3.85 lines/mm; Fine mode – 7.7 lines/mm.
  - Coding Scheme: MH.
  - Modem: V.29, V.27 ter with fall back function.
  - Modem Speed: 9600/7200/4800/2400 bps (automatically fall back).
  - Power Supply: Single phase 220V, model: 180-260V AC, 50/60Hz, Single phase.
  - Power Consumption: Standby: 6W ,Max: 90W.
  - Housing: It is housed in an elegant metal cabinet.
  - Power: 230VAC – Mains operated.
  - Operating Environment: Temperature: 5-400 C (41-950F).
  - Humidity: 45-85%.

We are leading manufacturers, suppliers of Facsimile Dynamic Demonstrator for Electronics Engineering Lab Equipments. Contact us to get high quality Facsimile Dynamic Demonstrator for Electronics Engineering Lab Equipments for schools, colleges, universities, research labs, laboratories and various industries.

```
{ "@context": "https://schema.org/", "@type": "Product", "name": "Facsimile Dynamic Demonstrator",
  "image": "http://www.schooleducationalinstrument.com/images/catalog/product/836669551Facsimile
  DynamicDemonstratorWithlogo.jpg", "description": "Facsimile Dynamic Demonstrator Specification:-
  • Scan Method: Horizontal -Contact Image Sensor, Vertical-intermittent Scanning by stepper Motor. •
  Document Size: Max – 216 X 1 000 mm , Min – 70 X 120 mm. • Document Thickness: 0.06 – 0.15
  mm. • Type: Desktop Transceiver. • Applicable Line: Public Switched Telephone Network. •
  Compatibility: CCITT Group 3. • Print Method: 0.06 – 0.15 mm. • Print Method: Thermal Printing. •
  Recording Paper Size: 216 mm X 15M, outer diameter=40mm. • Recording Width: 216 mm. •
  Resolution: Horizontal – 8 dots/mm; Vertical – Standard Mode – 3.85 lines/mm; Fine mode – 7.7
  lines/mm. • Coding Scheme: MH. • Modem: V.29, V.27 ter with fall back function. • Modem Speed:
  9600/7200/4800/2400 bps (automatically fall back). • Power Supply: Single phase 220V, model:
  180-260V AC, 50/60Hz, Single phase. • Power Consumption: Standby: 6W ,Max: 90W. • Housing: It
  is housed in an elegant metal cabinet. • Power: 230VAC – Mains operated. • Operating Environment:
  Temperature: 5-400 C (41-950F). • Humidity: 45-85%. We are leading manufacturers, suppliers of
  Facsimile Dynamic Demonstrator for Electronics Engineering Lab Equipments. Contact us to get high
  quality Facsimile Dynamic Demonstrator for Electronics Engineering Lab Equipments for schools,
  colleges, universities, research labs, laboratories and various industries.", "brand": "School Lab
  Instrument", "sku": "5", "gtin8": "5", "gtin13": "5", "gtin14": "5", "mpn": "5", "aggregateRating": {
  "@type": "AggregateRating", "ratingValue": "5", "bestRating": "5", "worstRating": "0", "ratingCount":
```

School Educational Instruments,  
Hargolal Road, Ambala Cantt, Haryana India  
Direct Contact Details  +91-8569909696  sales@schooleducationalinstrument.com  
 [www.schooleducationalinstrument.com](http://www.schooleducationalinstrument.com)