

Description

Capillary Tube Viscosimeter

The liquid whose flow characteristics are to be investigated is placed in a removable thermostatically controlled vessel which may be pressurised. The apparatus allows Poiseuille flows to be investigated and enables precise measurements to be made of the dynamic viscosities of liquids maintained at constant temperature, using the readings of a single pressure and a recorded time interval. The level of pressurisation of the vessel and the temperature of the liquid can be continuously varied as required ; the liquid is continuously stirred to ensure that its temperature is uniform. The vessel supplies a capillary tube which is also thermostatically controlled and interchangeable.

Technical Specifications:-

The following instrumentation is provided with the apparatus:

- A stopwatch for flow rate determination with a measuring cylinder.

-
- Capillary tube diameters : 0.2 and 0.4 mm.
 - Temperature range : ambient to 80°C to 0.5°C.
 - A thermostatically controlled vessel.
 - A mercury manometer.
 - A thermometer.
 - A magnetic stirrer.
 - Pressure range : 0 – 100 cm Hg.
 - Dimensions : 37 x 65 x 40 cm high (without manometer) or 120 cm high (with manometer).
 - Net weight : 20 kg.

We are leading manufacturers, suppliers of Capillary Tube Viscosimeter for Electronics Engineering Lab Equipments. Contact us to get high quality Capillary Tube Viscosimeter for Electronics Engineering Lab Equipments for schools, colleges, universities, research labs, laboratories and various industries.

School Educational Instruments,
Hargolal Road, Ambala Cantt, Haryana
India
Direct Contact Details 
+91-8569909696  sales@schooleducationalinstrument.com

www.schooleducationalinstrument.com