



Product Code . SEL-EELE-11266

Time Overcurrent Relay




Description

Time Overcurrent Relay

The relay parameters can be set manually or in conjunction with a PC via SCADA. Integrated program responsible for a self-test and the tripping test. The relay has three inverse current characteristics (normal, severely inverse and extremely inverse).

We are leading manufacturers, suppliers of Time Overcurrent Relay for Electronics Engineering Lab Equipments. Contact us to get high quality Time Overcurrent Relay for Electronics Engineering Lab Equipments for schools, colleges, universities, research labs, laboratories and various industries.

```
{ "@context": "https://schema.org/", "@type": "Product", "name": "Time Overcurrent Relay", "image": "http://www.schooleducationalinstrument.com/images/catalog/product/837387818TimeOvercurrentRelayWithlogo.jpg", "description": "Time Overcurrent Relay The relay parameters can be set manually or in conjunction with a PC via SCADA. Integrated program responsible for a self-test and the tripping test. The relay has three inverse current characteristics (normal, severely inverse and extremely inverse). We are leading manufacturers, suppliers of Time Overcurrent Relay for Electronics Engineering Lab Equipments. Contact us to get high quality Time Overcurrent Relay for Electronics Engineering Lab Equipments for schools, colleges, universities, research labs, laboratories and various industries.", "brand": "School Lab Instrument", "sku": "5", "gtin8": "5", "gtin13": "5", "gtin14": "5", "mpn": "5", "aggregateRating": { "@type": "AggregateRating", "ratingValue": "5", "bestRating": "5", "worstRating": "0", "ratingCount": "5" } }
```

Direct Contact Details  +91-8569909696  sales@schooleducationalinstrument.com
 www.schooleducationalinstrument.com